

# Material Safety Data Sheet



## 1. Identification of the material and supplier

### Names

Product name : Sikadur 52 Part B  
ADG : Corrosive liquid, n.o.s.

### Supplier

Supplier/Manufacturer : Sika Australia Pty. Ltd.  
55 Elizabeth Street  
(Locked Bag 482 BDC)  
Wetherill Park, NSW 2164  
Australia

Telephone no. : +61 2 9725 11 45

Fax no. : +61 2 9725 33 30

Emergency telephone number : +61 1800 033 111

Use of the substance/mixture : Chemical product for construction and industry

## 2. Hazards identification

Classification : Carc. Cat. 3; R40  
Xn; R20/21/22  
C; R34  
R43  
N; R51/53

Risk phrases : R40- Limited evidence of a carcinogenic effect.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R43- May cause sensitisation by skin contact.  
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases : S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S36/37/39- Wear suitable protective clothing, gloves and eye/face protection.  
S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

Statement of hazardous/dangerous nature : HAZARDOUS SUBSTANCE. DANGEROUS GOODS.

## 3. Composition/information on ingredients

Mixture : Yes.

benzyl alcohol	100-51-6	30 - <60
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	10 - <30
3,6-diazaoctanethylenediamin	112-24-3	10 - <30
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	1 - <10
naphthalene	91-20-3	1 - <10
bis[(dimethylamino)methyl]phenol	71074-89-0	1 - <10

Other ingredients, determined not to be hazardous according to Safe Work Australia criteria, and not dangerous according to the ADG Code, make up the product concentration to 100%.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 4 . First-aid measures

### First-aid measures

- Inhalation** : Get medical attention immediately. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Get medical attention immediately. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

## 5 . Fire-fighting measures

### Extinguishing media

- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- In a fire or if heated, a pressure increase will occur and the container may burst.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Hazchem code** : 2X

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

## 8 . Exposure controls/personal protection

### Occupational exposure limits

#### Ingredient name

naphthalene

#### Exposure limits

**Safe Work Australia (Australia, 8/2005).**

STEL: 79 mg/m<sup>3</sup> 15 minute(s).

STEL: 15 ppm 15 minute(s).

TWA: 52 mg/m<sup>3</sup> 8 hour(s).

TWA: 10 ppm 8 hour(s).

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

### Exposure controls

#### Engineering measures

- : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

## 8 . Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9 . Physical and chemical properties

- Physical state** : Liquid. [Liquid.]
- Colour** : Tan.
- Odour** : Amine-like.
- Vapour pressure** : 0.01 kPa (0.075 mm Hg) [20°C]
- Density** : 1 g/cm<sup>3</sup> [20°C (68°F)]
- Flash point** : Closed cup: 107°C (224.6°F)
- pH** : 11.6
- Solubility** : Insoluble in the following materials: cold water.

## 10 . Stability and reactivity

- Stability** : The product is stable.
- Conditions to avoid** : No specific data.
- Materials to avoid** : Reactive or incompatible with the following materials:  
acids
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11 . Toxicological information

### Potential acute health effects

- Inhalation** : Harmful by inhalation. May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.
- Skin contact** : Corrosive to the skin. Causes burns. Harmful in contact with skin. May cause sensitisation by skin contact.
- Eye contact** : Corrosive to eyes. Causes burns.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
-------------------------	--------	---------	------	----------

## 11 . Toxicological information

benzyl alcohol	LD50 Oral	Rat	1230 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>4.178 mg/l	4 hours
3-aminomethyl-3,5,5-trimethylcyclohexylamine	LD50 Dermal	Rat	1100 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
	LD50 Oral	Rat	1716 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol naphthalene	LD50 Oral	Rat	500 mg/kg	-
	LD50 Oral	Rat	500 mg/kg	-

**Conclusion/Summary** : Not available.

### Potential chronic health effects

#### Chronic toxicity

**Conclusion/Summary** : Not available.

#### Carcinogenicity

**Conclusion/Summary** : Not available.

#### Mutagenicity

**Conclusion/Summary** : Not available.

#### Teratogenicity

**Conclusion/Summary** : Not available.

#### Reproductive toxicity

**Conclusion/Summary** : Not available.

#### Chronic effects

: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### Carcinogenicity

: May cause cancer, based on animal data. Limited evidence of a carcinogenic effect. Risk of cancer depends on duration and level of exposure.

#### Mutagenicity

: No known significant effects or critical hazards.

#### Teratogenicity

: No known significant effects or critical hazards.

#### Developmental effects

: No known significant effects or critical hazards.

#### Fertility effects

: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Inhalation** : No specific data.

**Ingestion** : Adverse symptoms may include the following:  
stomach pains

**Skin** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur

**Eyes** : Adverse symptoms may include the following:  
pain  
watering  
redness

#### Target organs

: Contains material which may cause damage to the following organs: blood, kidneys, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea, nose/sinuses.

## 12 . Ecological information

**Environmental effects** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
3,6-diazaoctanethylenediamin	-	Acute EC50 10 to 100 mg/l	Daphnia	48 hours
	-	Acute EC50 10 to 100 mg/l	Algae	72 hours
	-	Acute LC50 >100 mg/l	Fish	96 hours

**Conclusion/Summary** : Not available.

## 12 . Ecological information

### Other ecological information

#### Biodegradability

**Conclusion/Summary** : Not available.

#### Bioaccumulative potential

<u>Product/ingredient name</u>	<u>LogP<sub>ow</sub></u>	<u>BCF</u>	<u>Potential</u>
benzyl alcohol	1.1	-	low
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	low
naphthalene	3.3	85.11380382	low

**Other adverse effects** : No known significant effects or critical hazards.

## 13 . Disposal considerations

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## 14 . Transport information

### ADG

**UN number** : UN1760  
**ADG Class** : 8  
**Packing group** : III  
**Proper shipping name** : Corrosive liquid, n.o.s.  
**Contains** : Triethylenetetramine/Isophoronediamine  
**Label No.** : 8  
**Hazchem code** : 2X

### ADR

**UN number** : UN1760  
**ADR Class** : 8  
**Classification code** : C9  
**Packing group** : III  
**Proper shipping name** : Corrosive liquid, n.o.s.  
**Contains** : Triethylenetetramine/Isophoronediamine  
**Label No.** : 8

### IMDG

**UN number** : UN1760  
**IMDG Class** : 8  
**Packing group** : III  
**Proper shipping name** : Corrosive liquid, n.o.s.  
**Contains** : Triethylenetetramine/Isophoronediamine  
**Emergency schedules (EmS)** : F-A, S-B  
**Marine pollutant** : Yes.  
**Label no.** : 8

### IATA

**UN number** : UN1760  
**IATA Class** : 8  
**Packing group** : III  
**Proper shipping name** : Corrosive liquid, n.o.s.

## 14 . Transport information

Contains : Triethylenetetramine/Isophoronediamine  
Label no. : 8

## 15 . Regulatory information

[Standard for the Uniform Scheduling of Drugs and Poisons](#)

6

[Control of Scheduled Carcinogenic Substances](#)

[Ingredient name](#)

[Schedule](#)

No listed substance

**Australia inventory (AICS)** : All components are listed or exempted.

**EU Classification** : Carc. Cat. 3; R40  
Xn; R20/21/22  
C; R34  
R43  
N; R51/53

## 16 . Other information

**Person who prepared the MSDS** : Validated by DeSilva on 27.03.2013.

**Date of previous issue** : No previous validation.

✔ Indicates information that has changed from previously issued version.

### Disclaimer

*Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: [www.sika.com.au](http://www.sika.com.au)*

*The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.*